## UTILITY LOCATOR 2 RTK

Built with RTK technology and compatible with a range of high-accuracy mapping solutions, the uber-accurate UtiliGuard 2 RTK brings centimeter-level accuracy to your utility mapping.

## **FEATURES & BENEFITS**

**CENTIMETER-LEVEL ACCURACY** Featuring RTK capabilities that are compatible with major third-party correction systems, this unit maps utilities with centimeter-level accuracy.

**HIGH-ACCURACY MAPPING** Compatible with third-party mapping solutions that allow you to map surface structures easily and accurately.

**INSTANT DATA TRANSFER** Get mapping-ready data easier by using the MyUtiliGuard and Subsite Realtime Mapping app to export your data directly to your GIS mapping program. **DATA STORAGE CAPACITY** Store up to one million data points locally on your unit, bringing you more flexibility to access your data across remote locations.

**OFFSET DEPTH VIEW** Measure horizontal and vertical distances for a utility that is not accessible from above with the offset depth view function.



## UTILIGUARD<sup>®</sup> 2 RTK UTILITY LOCATOR SPECIFICATIONS

| DIMENSIONS (RECEIVER)   | U.S.   | METRIC |
|---|--|--------|
| Height, max   | 27.7 in  | 703 mm |
| Length, max   | 14.2 in  | 361 mm |
| Width, max  | 4.8 in   | 122 mm |
| Operating weight, max   | 5.1 lb   | 2.3 kg |
| DIMENSIONS (TRANSMITTER)  |  |        |
| Height, max   | 10 in  | 254 mm |
| Length, max   | 12 in  | 305 mm |
| Width, max  | 7.8 in   | 198 mm |
| Operating weight, max   | 7.7 lb   | 3.5 kg |
| FEATURES  |  |        |
| Language support  | 19* user selectable languages  |        |
| Bluetooth® GPS connectivity   | Bluetooth 5.0 supporting BR, EDR 2/3 Mbps, eSCO, Bluetooth LE, and LE 2 Mbps |        |
| GPS start time, typical   |  |        |
| Cold  | 24 seconds   |        |
| Aided   | 4 seconds  |        |
| Hot   | 2 seconds  |        |
| BATTERY   |  |        |
| Batteries   | 2 D-Cell (LR20) or commercially available NiMH                               |        |
| Battery Life  | 8 hrs continuous / 16 hrs intermittent                                       |        |
| *Languages supported. Chinese, Czech, Danish, Dutch, English, Estonian, Einnish, Erench, German, Greek, Italian, Korean |  |        |

\*Languages supported: Chinese, Czech, Danish, Dutch, English, Estonian, Finnish, French, German, Greek, Italian, Korean, Latvian, Lithuanian, Polish, Portuguese, Russian, Spanish, Swedish.

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

